

## Aquapanel® Water Barrier

Technical Data Sheet 12/2023



# Aquapanel® Water Barrier

Moisture-permeable water barrier

### Product Description

AQUAPANEL® Water Barrier is a water resistant and wind tight membrane which provides superior air and moisture management

**Standards referred to**

### Fields of Application

It is used as a water conducting layer directly behind AQUAPANEL® Cement Board Outdoor where it prevents water, which finds a way behind the board, from ingressing into the wall.

### General Data

Description	Width (cm)	Length (m)	Packaging (rolls/pallet)	Material Number
Aquapanel® Water Barrier	150	50	50	544043

### Technical Data

Description	
Width (cm)	150
Length (m)	50
Thickness approx. (mm)	0,5
Equivalent thickness of air approx (m)	0,03
Reaction to fire	E (EN 13501-1, on mineral wool and wood)
Weight per unit area	approx. 130 g/m <sup>2</sup>
Colour	front side black, back side white

### System Performance Values

Performance values as sound insulation, fire resistance etc. may differ acc. to the drywall system to be applied. Please check the performance values of the drywall systems;

[Knauf Technical Website](#)

[Document Center](#)

### Application

Application should be done acc. to the applicable standards (TS 1475) and acc. to the Knauf Technical Brochures of the respective drywall system.

▶ 444 YAPI - 9274

▶ [www.knauf.com.tr](http://www.knauf.com.tr) / [www.teknik.knauf.com.tr](http://www.teknik.knauf.com.tr)

▶ [teknik@knauf.com](mailto:teknik@knauf.com)

Center: Knauf Moment Beştepe Office, Beştepe Mah. 32.Cadde No:1/212-218 06560 Beştepe-Yenimahalle  
/ ANKARA Tel: 0312 297 0100 Faks: 0312 266 4506