

Declaration of Performance

Gyproc® Sealant



1 Unique identification code of the product type:	Gyproc Sealant
2 Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):	Gyproc Sealant
3 Intended use/s:	F-INT acrylic sealant and adhesive used for sealing small air gaps
4 Manufacturer:	British Gypsum Registered in England 734396 East Leake, Loughborough, Leicestershire LE12 6HX Tel: +44 (0) 115 945 1000
5 Authorised representative:	N/A
6 System/s of AVCP:	System 4
7 Harmonised standard:	BS EN 15651-1:2012
Notified body/ies:	N/A
8 European Assessment Document:	N/A
European Technical Assessment:	N/A
Technical Assessment Body:	N/A
Notified body/ies:	N/A
9 Declared performance/s:	The characteristics in the table below apply to all products mentioned in 2 above.


Essential characteristics	Performance	Harmonised technical specification
Reaction to Fire (R2F)	Class E	BS EN 15651-1:2012
Water tightness and air-tightness determined by:		
Resistance to flow (mm)	≤5	BS EN 15651-1:2012
Loss of volume (%)	≤45	BS EN 15651-1:2012
Tensile properties: Elongation at break at 23°C (%) ¹	≥25	BS EN 15651-1:2012
Durability	Pass	BS EN 15651-1:2012

¹ Conditioning Procedure A (according to ISO 8339), Tested on Mortar M2 Substrate, no primer.

10 Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



.....
Matt Pullen, Managing Director, British Gypsum

East Leake 04/08/2019

.....
Place and date of issue