




553A2400

GALLERY



PRODUCT ATTRIBUTES

Brand	Expamet
Generic Ref	553
Product Range	Plasterers Accessories

Product Sub-range	Skim-coat plaster beads - Internal Use
Product Type	Angle Bead
European Standard/ETA	BS EN14353:2007+A1:2010
DoP Ref	EXP073CPR2013
Material	Galvanized Mild Steel DX51D+Z275 to EN10346:2015
Coating/Finish/Colour	275g/m ² Zinc Coating
Length 1/Projection	2400mm
Width/Wing Length	22mm Wing length
Plaster/Render/Joist depth	2-3mm Plaster Depth
Material Gauge	0.4mm
Individual Weight (kg)	0.268
Fire Rating	Reaction to fire: Class A1
Fixing Hole Dimensions	3.2mm
Fixing Type	Galvanized Clout Nails/Staples/Grab Adhesive/Plaster
Installation requirement 1	Fix at intervals not exceeding 600mm
Installation requirement 2	Avoid damage to beads when trowelling. Do not use abrasives to clean beads.
Unit of Sale EAN	5014316004640
Sales Qty	50
Packaging material	Cardboard
Carton Ref	XBP553A2410
Carton/Size	130 x 32 x 2410
Packaging weight	0
Packaged transit weight	13.4
Features/Benefits 1	Perforated wing provides a key to prevent cracking
Features/Benefits 2	Fixing holes to suit a standard plasterboard nail
Features/Benefits 3	Provides a clean straight corner and protects plaster edges from damage
Features/Benefits 4	Can easily be cut to size using tin-snips or aviation cutters

HEALTH AND SAFETY INFORMATION

1. Identification

'Expamet'
Birtley Group Ltd
Mary Ave,
Birtley,
DH3 1JF
UNITED KINGDOM
(0191) 410 6631

2. Composition

Galvanized Mild Steel DX51D+Z275 to EN10346:2015

3. Hazards Identification

Possible cuts from sharp steel edges.
Toxic and irritant fumes from high temperatures

4. First aid measures

Skin and eye contact: Treat cuts from steel edges as required.
Ingestion: Not applicable.
Inhalation: Remove from source of fumes and dust.

5. Fire fighting measures

Non-flammable material.

6. Accidental release measures

Not applicable.

7. Handling and storage

Bands and straps must not be used for lifting.
Use suitable PPE when handling products.
Assess manual handling risks before lifting.
Products should be stacked on firm level ground in dry conditions.

8. Exposure controls

Wear personal protection such as gloves and safety goggles when handling products.
Some products may have a film of soluble cutting fluid after manufacture; therefore carry out personal hygiene including proper washing of hands, after contact.

9. Physical and chemical properties

Products are supplied in various lengths, widths and gauges.
Metallic grey appearance.

10. Stability and reactivity

Products are stable under normal conditions but if subjected to high temperatures, fumes are produced.

11. Toxicological information

High temperatures can produce fumes.

12. Ecological information

No known Hazard.

13. Disposal considerations

Recycle or dispose of in accordance with Waste Management Licensing Regulations.

14. Transport information

Not classified as hazardous for transport.

15. Regulatory information

Products are articles and have no registration obligation under REACH.

16. Other information

All products must be installed in accordance with Expamet Building Products' published instructions.

Where structural products are to be removed from an existing installation, care must be taken to ensure that the procedure followed does not compromise the loading/installation restrictions applicable to the products.

Actual fixing installations must comply with current Health and Safety requirements.