

## TECHNICAL DATASHEET

**Introduction:** **UltraLite 60:15** is an **IFC Certified** ultra lightweight symmetrical fire rated cavity barrier designed to provide compartmentation in roof cavities and concealed spaces for both vertical and horizontal applications.

**UltraLite 60:15** is simple to fit and requires no specialist tools or fittings.

**Physical Properties:**

Description:	Lightweight / Health Safe / User friendly / flexible / durable / Easy to shape and cut
Colour:	White
Proprietary Treatment:	Food safe and non-corrosive.
Thickness:	6.5 mm
Weight:	1334 g/m <sup>2</sup> -
Fibre Diameter	> 6 micron, (classified non-respirable)

**Certification Body:** **IFC** Certification Reference # **1336**

**Testing Authority:** **Warringtonfire**

<b>Test Specification:</b>	<b>Test Classification:</b>	<b>BS 476: parts 20/22</b>	<b>60 minutes integrity 15 minutes insulation</b>
	<b>Test Report:</b>	<b>376403 [ Vertical ] 419257 [ Horizontal ]</b>	Review date: Jan 2022 Review date: Nov 2024

**Packing Specification and Pack Dimensions:**

Width:	130cm	Packaging: Convoluted and individually wrapped in polythene.
Roll Length:	6m	
Roll Area:	7.8m <sup>2</sup>	Packed in strong boxes.
Pack Weight:	10.4kgs	
Quantity per box:	10 packs	
Quantity per pallet:	2 boxes (20 packs)	