

DECLARATION OF PERFORMANCE

Document No. 0004-CPR UK-22v1
insulation-uk.com/dop

**UK
CA**

1. Unique identification code of the product-type:

Spacesaver
Spacesaver Plus
Spacesaver Ready-Cut
Spacesaver Lite

2. Intended use/es:

Thermal Insulation for Buildings (ThIB)

3. Manufacturer:

Saint-Gobain Isover UK Limited,
Whitehouse Industrial Estate,
Runcorn, Cheshire, WA7 3DP, UK

4. Authorised representative:

N/A

5. System/s of AVCP:

System 1 (Reaction to Fire) and System 3

6. Designated Standard:

BS EN 13162:2012 + A1:2015

Approved body/ies:

Approved body Warringtonfire Testing and Certification Limited No.1121 performed, carried out the determination of the product type, the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of constancy of performance (1121-CPR-7001) for Reaction to fire.

7. Declared performance/s:

Harmonised Technical Specification: BS EN 13162:2012 + A1:2015

Essential characteristics	Performance	Unit	Declared Performance						
Product name			Spacesaver				Spacesaver Plus		
Reaction to fire		Euroclass	A1						
Release of dangerous substances to the indoor environment	Release of dangerous substances (e)		NPD						
Acoustic absorption index	Sound absorption		NPD						
Impact noise transmission index	Dynamic stiffness		NPD						
	Thickness		NPD						
	Compressibility		NPD						
	Air flow resistivity		NPD						
Direct airborne sound insulation index	Air flow resistivity		NPD						
Continuous glowing combustion	Continuous glowing combustion (e)		NPD						
Thermal resistance	Thermal resistance	m ² .K/W	2.25	3.40	3.85	4.50	2.50	3.75	5.00
	Thermal conductivity	W/m.K	0.044	0.044	0.044	0.044	0.040	0.040	0.040
	Thickness	mm	100	150	170	200	100	150	200
	Thickness class		T1	T1	T1	T1	T1	T1	T1
Water permeability	Short term water absorption		NPD						
	Long term water absorption		NPD						
Water vapour permeability	Water vapour transmission		NPD						
Compressive strength	Compressive stress or compressive strength		NPD						
	Point load		NPD						
Durability of Reaction to fire against heat, weathering, ageing/degradation	Durability characteristics (a)	Euroclass	A1						
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance (b)	m ² .K/W	2.25	3.40	3.85	4.50	2.50	3.75	5.00
	Thermal conductivity (b)	W/m.K	0.044	0.044	0.044	0.044	0.040	0.040	0.040
	Durability characteristics (c)		NPD						
Tensile/flexural strength	Tensile strength perpendicular to faces (d)		NPD						
Durability of compressive strength against heat, weathering, ageing/degradation	Compressive creep		NPD						

NPD = No Performance Determined

- (a) No change in Reaction to fire properties for mineral wool products. The fire performance of mineral wool does not deteriorate with time. The Euroclass classification of the product is related to the organic content, which cannot increase with time.
- (b) Thermal conductivity of mineral wool products does not change with time.
- (c) For dimensional stability thickness only.
- (d) This characteristic also covers handling and installation.
- (e) European test methods are under development.

0004-CPR UK-22v1

Isover reserves the right to alter or amend product specification without notice. The information given in this publication is correct to the best of our knowledge at the time of publication. Whilst Isover will endeavor to ensure publications are up to date, it is the users responsibility to check with us that it is correct prior to use.

7. Declared performance/s:

Harmonised Technical Specification: BS EN 13162:2012 + A1:2015

Essential characteristics	Performance	Unit	Declared Performance					
Product name			Spacesaver Ready-Cut (3x386)			Spacesaver Ready-Cut (2x580)		
Reaction to fire		Euroclass	A1					
Release of dangerous substances to the indoor environment	Release of dangerous substances (e)		NPD					
Acoustic absorption index	Sound absorption		NPD					
Impact noise transmission index	Dynamic stiffness		NPD					
	Thickness		NPD					
	Compressibility		NPD					
	Air flow resistivity		NPD					
Direct airborne sound insulation index	Air flow resistivity		NPD					
Continuous glowing combustion	Continuous glowing combustion (e)		NPD					
Thermal resistance	Thermal resistance	m ² .K/W	2.25	3.40	4.50	2.25	3.40	4.50
	Thermal conductivity	W/m.K	0.044	0.044	0.044	0.044	0.044	0.044
	Thickness	mm	100	150	200	100	150	200
	Thickness class		T1	T1	T1	T1	T1	T1
Water permeability	Short term water absorption		NPD					
	Long term water absorption		NPD					
Water vapour permeability	Water vapour transmission		NPD					
Compressive strength	Compressive stress or compressive strength		NPD					
	Point load		NPD					
Durability of Reaction to fire against heat, weathering, ageing/degradation	Durability characteristics (a)	Euroclass	A1					
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance (b)	m ² .K/W	2.25	3.40	4.50	2.25	3.40	4.50
	Thermal conductivity (b)	W/m.K	0.044	0.044	0.044	0.044	0.044	0.044
	Durability characteristics (c)		NPD					
Tensile/flexural strength	Tensile strength perpendicular to faces (d)		NPD					
Durability of compressive strength against heat, weathering, ageing/degradation	Compressive creep		NPD					

NPD = No Performance Determined

- (a) No change in Reaction to fire properties for mineral wool products.
The fire performance of mineral wool does not deteriorate with time.
The Euroclass classification of the product is related to the organic content, which cannot increase with time.
- (b) Thermal conductivity of mineral wool products does not change with time.
- (c) For dimensional stability thickness only.
- (d) This characteristic also covers handling and installation.
- (e) European test methods are under development.

0004-CPR UK-22v1

7. Declared performance/s:

Harmonised Technical Specification: BS EN 13162:2012 + A1:2015

Essential characteristics	Performance	Unit	Declared Performance			
Product name			Spacesaver Lite			
Reaction to fire		Euroclass	A1			
Release of dangerous substances to the indoor environment	Release of dangerous substances (e)		NPD			
Acoustic absorption index	Sound absorption		NPD			
Impact noise transmission index	Dynamic stiffness		NPD			
	Thickness		NPD			
	Compressibility		NPD			
	Air flow resistivity		NPD			
Direct airborne sound insulation index	Air flow resistivity		NPD			
Continuous glowing combustion	Continuous glowing combustion (e)		NPD			
Thermal resistance	Thermal resistance	m ² .K/W	2.25	3.40	3.85	4.50
	Thermal conductivity	W/m.K	0.044	0.044	0.044	0.044
	Thickness	mm	100	150	170	200
	Thickness class		T1	T1	T1	T1
Water permeability	Short term water absorption		NPD			
	Long term water absorption		NPD			
Water vapour permeability	Water vapour transmission		NPD			
Compressive strength	Compressive stress or compressive strength		NPD			
	Point load		NPD			
Durability of Reaction to fire against heat, weathering, ageing/degradation	Durability characteristics (a)	Euroclass	A1			
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance (b)	m ² .K/W	2.25	3.40	3.85	4.50
	Thermal conductivity (b)	W/m.K	0.044	0.044	0.044	0.044
	Durability characteristics (c)		NPD			
Tensile/flexural strength	Tensile strength perpendicular to faces (d)		NPD			
Durability of compressive strength against heat, weathering, ageing/degradation	Compressive creep		NPD			

NPD = No Performance Determined

- (a) No change in Reaction to fire properties for mineral wool products.
The fire performance of mineral wool does not deteriorate with time.
The Euroclass classification of the product is related to the organic content, which cannot increase with time.
- (b) Thermal conductivity of mineral wool products does not change with time.
- (c) For dimensional stability thickness only.
- (d) This characteristic also covers handling and installation.
- (e) European test methods are under development.

0004-CPR UK-22v1

Isover reserves the right to alter or amend product specification without notice.
The information given in this publication is correct to the best of our knowledge at the time of publication. Whilst Isover will endeavor to ensure publications are up to date, it is the users responsibility to check with us that it is correct prior to use.

8. Appropriate technical documentation and/or specific technical documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

A handwritten signature in black ink, appearing to read 'Dean O'Sullivan', written in a cursive style.

**Dean O'Sullivan
Managing Director
Runcorn.
24th November 2022**

0004-CPR UK-22v1

Isover reserves the right to alter or amend product specification without notice.
The information given in this publication is correct to the best of our knowledge
at the time of publication. Whilst Isover will endeavor to ensure publications are
up to date, it is the users responsibility to check with us that it is correct prior to use.