

Product Data Sheet

Knauf Windliner Screws



Specialist terracotta-coloured low profile headed screws for attachment of Knauf Windliner boards to the solid steel frame.

Areas of Application

Fixing Windliner board to mild steel structural framing system members (up to a maximum capacity of 2.5mm).

For steel above 2.5mm thickness it is recommended to pre-drill before using Windliner Screws.

Key Benefits

- 500 hour salt spray corrosion resistance
- For use in conjunction with Knauf Windliner board
- Bugle Countersunk head to sit flush on Windliner Board
- Certified on Windliner and Throughwall BBA's

Compliance Standards

BS EN 14566: 2008 & A1: 2009

Performance Data

Reaction to Fire (R2F)	Flexural Strength
A1	Pass

Technical information

Dimensions and Weights										
Length (mm)	Diameter (mm)	Colour	Screw head type	Suitable Substrates	Fixing Capacity (mm)	Coating Type	Coating thickness (µm)	Salt spray tested (Y/N)	If Y how long? (per h)	Material Number
25.00	3.50	Terracotta	Bulge countersinking	Steel	13	Organic: Aluminium & Zinc Flake bound in baked Resin	14	Y	500	525996
38.00	3.50	Terracotta	Bulge countersinking	Steel	26	Organic: Aluminium & Zinc Flake bound in baked Resin	14	Y	500	525997

Creation Date: 08/06/2023
 Revision Reference: 001
 Revision Date: 08/06/2023

Build for the world we live in

Sustainability

Total Recycled Content

Up to 95%

Recyclability

Full recyclable

Storage and Handling

Must be kept indoors during storage in dry, non-humid area and safe from premature exposure to moisture or wetting before use.

Packaging

Box (recycled cardboard).

Disposal/Repair

In accordance with local regulations, please recycle where possible.

Health & Safety

Please refer to our Safety Data Sheet for guidance on Personal Protection Equipment required for the handling and installation of this product.

Application / Installation

Install countersunk. Head should be flush with the surface of the board.

Over driving may result in failure of the fastener or strip out of the work surface.

Additional Documentation

[Declaration of Performance UKCA](#)

[Declaration of Performance CE](#)

[Safety Data Sheet](#)



Customer Service

UK Tel: 0800 521 050
Eire Tel: 01 4620739
Email: cservice@knauf.com

Technical Service

0800 521050 (option 2)
Live Webchat 09:00 -17:00
technical-uk@knauf.com

Website

www.knauf.co.uk
www.knauf.ie

Address

Knauf
Kemsley Fields Business Park
Sittingbourne
Kent ME9 8SR

KML100488

The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued.

© Copyright Knauf 2023

Creation Date: 08/06/2023
Revision Reference: 001
Revision Date: 08/06/2023

Build for the world we live in