

Declaration of Performance

R4208JPCPR

1. Unique identification code of the product-type:
BUILDING SLAB RS33 UNIVERSAL SLAB RS33, Rocksilk® Flexible Slab, FLEXIBLE SLAB 400 ECOSE SPACE 4 SLAB, ECOSE SPACE 4 SLAB, ECOSE CAVITY SLAB, RS35 (BLX), DRITHERM CAVITY SLAB, ROOFMAX 30 (INC/EX TF), ECOBATT ROOFMAX 30 (INC/EX TF), KRIMPACT Façade SLAB, ROOFMAX 30 PLUS, ECOSE FLEXIBLE SLAB, Rocksilk® Fabrication slab, TERMOCOFRAGE
2. Intended use or uses:
Thermal Insulation for Buildings (ThIB)
3. Manufacturer:
Knauf Insulation Ltd.
Chemistry Lane, CH5 2DA Queensferry, Flintshire
UK
www.knaufinsulation.com - dop@knaufinsulation.com
4. Authorised representative:
Knauf Insulation AB
Gardatorget 1
412 50 Goteborg
Sweden
5. System or systems of assessment and verification of constancy of performance:
AVCP System 1 for Reaction to Fire
AVCP System 3 for the other characteristics
- 6a. Harmonized Standard:

EN 13162:2012 + A1:2015

Notified body or bodies:
AVCP System 1: (Notified certification body) 0751 - Forschungsinstitut für Wärmeschutz e. V. München
FIW München - - -

AVCP System 3: (Notified testing laboratory) 0751 - Forschungsinstitut für Wärmeschutz e. V. München
FIW München - - - - - - - -
- 6b. European Assessment document: not applicable
European Technical Assessment: not applicable
Technical Assessment Body: not applicable
Notified body/ies: not applicable
7. Declared Performances:
See next page

Essential Characteristics	R4208JPCPR		Harmonised technical standard
	Performance {f}	BUILDING SLAB RS33 UNIVERSAL SLAB RS33	
Thermal Resistance	Thermal conductivity (W/mK)	λ_D 0,037	EN 13162:2012 + A1:2015
	Thermal Resistance	See performance chart	
	Thickness range (mm)	30-<50 50-200	
	Thickness tolerance	T2 T4	
Reaction to Fire	Reaction to fire	A1 A1	
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability Characteristics	NPD {a}	
Durability of thermal resistance against heat, weathering, ageing / degradation	Thermal Resistance	NPD{b}	
	Thermal conductivity	NPD	
	Durability characteristics	NPD {c}	
Compressive Strength	Compressive Stress / Compressive Strength	NPD	
	Point Load	NPD	
Tensile / Flexural strength	Tensile strength perpendicular faces	NPD {d}	
Durability of compressive Strength against ageing / degradation	Compressive creep	NPD	
Water Permeability	Short term water absorption	NPD	
	Long term water absorption	NPD	
Water vapour permeability	Water vapour transmission, water vapour diffusion resistance factor	MU1 MU1	
Impact noise transmissions index (for floors)	Dynamic stiffness	NPD	
	Thickness	NPD	
	Compressibility	NPD	
	Air flow resistivity	NPD	
Acoustic absorptions index	Sound absorption	NPD	
Direct airborne sound insulation index	Air flow resistivity	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD {e}	
Continuous glowing combustion	Continuous glowing combustion	NPD {e}	
NPD - No performance determined			

Essential Characteristics	R4208JPCPR		Harmonised technical standard
	Performance {f}	DRITHERM CAVITY SLAB	
Thermal Resistance	Thermal conductivity (W/mK)	λ_D 0,037	EN 13162:2012 + A1:2015
	Thermal Resistance	See performance chart	
	Thickness range (mm)	30-<50 50-200	
	Thickness tolerance	T2 T4	
Reaction to Fire	Reaction to fire	A1 A1	
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability Characteristics	NPD {a}	
Durability of thermal resistance against heat, weathering, ageing / degradation	Thermal Resistance	NPD{b}	
	Thermal conductivity	NPD	
	Durability characteristics	NPD {c}	
Compressive Strength	Compressive Stress / Compressive Strength	NPD	
	Point Load	NPD	
Tensile / Flexural strength	Tensile strength perpendicular faces	NPD {d}	
Durability of compressive Strength against ageing / degradation	Compressive creep	NPD	
Water Permeability	Short term water absorption	WS WS	
	Long term water absorption	NPD	
Water vapour permeability	Water vapour transmission, water vapour diffusion resistance factor	MU1 MU1	
Impact noise transmissions index (for floors)	Dynamic stiffness	NPD	
	Thickness	NPD	
	Compressibility	NPD	
	Air flow resistivity	NPD	
Acoustic absorptions index	Sound absorption	NPD	
Direct airborne sound insulation index	Air flow resistivity	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD {e}	
Continuous glowing combustion	Continuous glowing combustion	NPD {e}	
NPD - No performance determined			

Essential Characteristics	R4208JPCPR		Harmonised technical standard
	Performance {f}	ECOBATT ROOFMAX 30 (INC/EX TF)	
Thermal Resistance	Thermal conductivity (W/mK)	λ_D 0,037	EN 13162:2012 + A1:2015
	Thermal Resistance	See performance chart	
	Thickness range (mm)	50-200	
	Thickness tolerance	T5	
Reaction to Fire	Reaction to fire	A1	
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability Characteristics	NPD {a}	
Durability of thermal resistance against heat, weathering, ageing / degradation	Thermal Resistance	NPD{b}	
	Thermal conductivity	NPD	
	Durability characteristics	NPD {c}	
Compressive Strength	Compressive Stress / Compressive Strength	NPD	
	Point Load	NPD	
Tensile / Flexural strength	Tensile strength perpendicular faces	NPD {d}	
Durability of compressive Strength against ageing / degradation	Compressive creep	NPD	
Water Permeability	Short term water absorption	WS	
	Long term water absorption	NPD	
Water vapour permeability	Water vapour transmission, water vapour diffusion resistance factor	MU1	
Impact noise transmissions index (for floors)	Dynamic stiffness	NPD	
	Thickness	NPD	
	Compressibility	NPD	
	Air flow resistivity	NPD	
Acoustic absorptions index	Sound absorption	NPD	
Direct airborne sound insulation index	Air flow resistivity	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD {e}	
Continuous glowing combustion	Continuous glowing combustion	NPD {e}	
NPD - No performance determined			

Essential Characteristics	R4208JPCPR		Harmonised technical standard
	Performance {f}	ECOSE CAVITY SLAB	
Thermal Resistance	Thermal conductivity (W/mK)	λ_D 0,037	EN 13162:2012 + A1:2015
	Thermal Resistance	See performance chart	
	Thickness range (mm)	50-200	
	Thickness tolerance	T4	
Reaction to Fire	Reaction to fire	A1	
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability Characteristics	NPD {a}	
Durability of thermal resistance against heat, weathering, ageing / degradation	Thermal Resistance	NPD{b}	
	Thermal conductivity	NPD	
	Durability characteristics	NPD {c}	
Compressive Strength	Compressive Stress / Compressive Strength	NPD	
	Point Load	NPD	
Tensile / Flexural strength	Tensile strength perpendicular faces	NPD {d}	
Durability of compressive Strength against ageing / degradation	Compressive creep	NPD	
Water Permeability	Short term water absorption	WS	
	Long term water absorption	NPD	
Water vapour permeability	Water vapour transmission, water vapour diffusion resistance factor	MU1	
Impact noise transmissions index (for floors)	Dynamic stiffness	NPD	
	Thickness	NPD	
	Compressibility	NPD	
	Air flow resistivity	NPD	
Acoustic absorptions index	Sound absorption	NPD	
Direct airborne sound insulation index	Air flow resistivity	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD {e}	
Continuous glowing combustion	Continuous glowing combustion	NPD {e}	
NPD - No performance determined			

Essential Characteristics	R4208JPCPR		Harmonised technical standard
	Performance {f}	ECOSE FLEXIBLE SLAB	
Thermal Resistance	Thermal conductivity (W/mK)	λ_D 0,037	EN 13162:2012 + A1:2015
	Thermal Resistance	See performance chart	
	Thickness range (mm)	50-200	
	Thickness tolerance	T4	
Reaction to Fire	Reaction to fire	A1	
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability Characteristics	NPD {a}	
Durability of thermal resistance against heat, weathering, ageing / degradation	Thermal Resistance	NPD{b}	
	Thermal conductivity	NPD	
	Durability characteristics	NPD {c}	
Compressive Strength	Compressive Stress / Compressive Strength	NPD	
	Point Load	NPD	
Tensile / Flexural strength	Tensile strength perpendicular faces	NPD {d}	
Durability of compressive Strength against ageing / degradation	Compressive creep	NPD	
Water Permeability	Short term water absorption	NPD	
	Long term water absorption	NPD	
Water vapour permeability	Water vapour transmission, water vapour diffusion resistance factor	MU1	
Impact noise transmissions index (for floors)	Dynamic stiffness	NPD	
	Thickness	NPD	
	Compressibility	NPD	
	Air flow resistivity	NPD	
Acoustic absorptions index	Sound absorption	NPD	
Direct airborne sound insulation index	Air flow resistivity	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD {e}	
Continuous glowing combustion	Continuous glowing combustion	NPD {e}	
NPD - No performance determined			

Essential Characteristics	R4208JPCPR		Harmonised technical standard
	Performance {f}	ECOSE SPACE 4 SLAB	
Thermal Resistance	Thermal conductivity (W/mK)	λ_D 0,037	EN 13162:2012 + A1:2015
	Thermal Resistance	See performance chart	
	Thickness range (mm)	30-<50	
	Thickness tolerance	T2 T4	
Reaction to Fire	Reaction to fire	A1 A1	
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability Characteristics	NPD {a}	
Durability of thermal resistance against heat, weathering, ageing / degradation	Thermal Resistance	NPD{b}	
	Thermal conductivity	NPD	
	Durability characteristics	NPD {c}	
Compressive Strength	Compressive Stress / Compressive Strength	NPD	
	Point Load	NPD	
Tensile / Flexural strength	Tensile strength perpendicular faces	NPD {d}	
Durability of compressive Strength against ageing / degradation	Compressive creep	NPD	
Water Permeability	Short term water absorption	NPD	
	Long term water absorption	NPD	
Water vapour permeability	Water vapour transmission, water vapour diffusion resistance factor	MU1 MU1	
Impact noise transmissions index (for floors)	Dynamic stiffness	NPD	
	Thickness	NPD	
	Compressibility	NPD	
	Air flow resistivity	NPD	
Acoustic absorptions index	Sound absorption	NPD	
Direct airborne sound insulation index	Air flow resistivity	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD {e}	
Continuous glowing combustion	Continuous glowing combustion	NPD {e}	
NPD - No performance determined			

Essential Characteristics	R4208JPCPR		Harmonised technical standard
	Performance {f}	FLEXIBLE SLAB 400 ECOSE SPACE 4 SLAB	
Thermal Resistance	Thermal conductivity (W/mK)	λ_D 0,037	EN 13162:2012 + A1:2015
	Thermal Resistance	See performance chart	
	Thickness range (mm)	30-<50 50-200	
	Thickness tolerance	T2 T4	
Reaction to Fire	Reaction to fire	A1 A1	
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability Characteristics	NPD {a}	
Durability of thermal resistance against heat, weathering, ageing / degradation	Thermal Resistance	NPD{b}	
	Thermal conductivity	NPD	
	Durability characteristics	NPD {c}	
Compressive Strength	Compressive Stress / Compressive Strength	NPD	
	Point Load	NPD	
Tensile / Flexural strength	Tensile strength perpendicular faces	NPD {d}	
Durability of compressive Strength against ageing / degradation	Compressive creep	NPD	
Water Permeability	Short term water absorption	NPD	
	Long term water absorption	NPD	
Water vapour permeability	Water vapour transmission, water vapour diffusion resistance factor	MU1 MU1	
Impact noise transmissions index (for floors)	Dynamic stiffness	NPD	
	Thickness	NPD	
	Compressibility	NPD	
	Air flow resistivity	NPD	
Acoustic absorptions index	Sound absorption	NPD	
Direct airborne sound insulation index	Air flow resistivity	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD {e}	
Continuous glowing combustion	Continuous glowing combustion	NPD {e}	
NPD - No performance determined			

Essential Characteristics	R4208JPCPR		Harmonised technical standard
	Performance {f}	KRIMPACT Façade SLAB	
Thermal Resistance	Thermal conductivity (W/mK)	λ_D 0,037	EN 13162:2012 + A1:2015
	Thermal Resistance	See performance chart	
	Thickness range (mm)	25-<50 50-100	
	Thickness tolerance	T2 T4	
Reaction to Fire	Reaction to fire	A1 A1	
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability Characteristics	NPD {a}	
Durability of thermal resistance against heat, weathering, ageing / degradation	Thermal Resistance	NPD{b}	
	Thermal conductivity	NPD	
	Durability characteristics	NPD {c}	
Compressive Strength	Compressive Stress / Compressive Strength	NPD	
	Point Load	NPD	
Tensile / Flexural strength	Tensile strength perpendicular faces	NPD {d}	
Durability of compressive Strength against ageing / degradation	Compressive creep	NPD	
Water Permeability	Short term water absorption	WS WS	
	Long term water absorption	NPD	
Water vapour permeability	Water vapour transmission, water vapour diffusion resistance factor	MU1 MU1	
Impact noise transmissions index (for floors)	Dynamic stiffness	NPD	
	Thickness	NPD	
	Compressibility	NPD	
	Air flow resistivity	NPD	
Acoustic absorptions index	Sound absorption	NPD	
Direct airborne sound insulation index	Air flow resistivity	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD {e}	
Continuous glowing combustion	Continuous glowing combustion	NPD {e}	
NPD - No performance determined			

Essential Characteristics	R4208JPCPR		Harmonised technical standard
	Performance {f}	Rocksilk® Fabrication slab	
Thermal Resistance	Thermal conductivity (W/mK)	λ_D 0,037	EN 13162:2012 + A1:2015
	Thermal Resistance	See performance chart	
	Thickness range (mm)	50-200	
	Thickness tolerance	T4	
Reaction to Fire	Reaction to fire	A1	
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability Characteristics	NPD {a}	
Durability of thermal resistance against heat, weathering, ageing / degradation	Thermal Resistance	NPD{b}	
	Thermal conductivity	NPD	
	Durability characteristics	NPD {c}	
Compressive Strength	Compressive Stress / Compressive Strength	NPD	
	Point Load	NPD	
Tensile / Flexural strength	Tensile strength perpendicular faces	NPD {d}	
Durability of compressive Strength against ageing / degradation	Compressive creep	NPD	
Water Permeability	Short term water absorption	NPD	
	Long term water absorption	NPD	
Water vapour permeability	Water vapour transmission, water vapour diffusion resistance factor	MU1	
Impact noise transmissions index (for floors)	Dynamic stiffness	NPD	
	Thickness	NPD	
	Compressibility	NPD	
	Air flow resistivity	NPD	
Acoustic absorptions index	Sound absorption	NPD	
Direct airborne sound insulation index	Air flow resistivity	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD {e}	
Continuous glowing combustion	Continuous glowing combustion	NPD {e}	
NPD - No performance determined			

Essential Characteristics	R4208JPCPR		Harmonised technical standard
	Performance {f}	Rocksilk® Flexible Slab	
Thermal Resistance	Thermal conductivity (W/mK)	λ_D 0,037	EN 13162:2012 + A1:2015
	Thermal Resistance	See performance chart	
	Thickness range (mm)	30-<50 50-200	
	Thickness tolerance	T2 T4	
Reaction to Fire	Reaction to fire	A1 A1	
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability Characteristics	NPD {a}	
Durability of thermal resistance against heat, weathering, ageing / degradation	Thermal Resistance	NPD{b}	
	Thermal conductivity	NPD	
	Durability characteristics	NPD {c}	
Compressive Strength	Compressive Stress / Compressive Strength	NPD	
	Point Load	NPD	
Tensile / Flexural strength	Tensile strength perpendicular faces	NPD {d}	
Durability of compressive Strength against ageing / degradation	Compressive creep	NPD	
Water Permeability	Short term water absorption	NPD	
	Long term water absorption	NPD	
Water vapour permeability	Water vapour transmission, water vapour diffusion resistance factor	MU1 MU1	
Impact noise transmissions index (for floors)	Dynamic stiffness	NPD	
	Thickness	NPD	
	Compressibility	NPD	
	Air flow resistivity	NPD	
Acoustic absorptions index	Sound absorption	NPD	
Direct airborne sound insulation index	Air flow resistivity	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD {e}	
Continuous glowing combustion	Continuous glowing combustion	NPD {e}	
NPD - No performance determined			

Essential Characteristics	R4208JPCPR		Harmonised technical standard
	Performance {f}	ROOFMAX 30 (INC/EX TF)	
Thermal Resistance	Thermal conductivity (W/mK)	λ_D 0,037	EN 13162:2012 + A1:2015
	Thermal Resistance	See performance chart	
	Thickness range (mm)	50-200	
	Thickness tolerance	T5	
Reaction to Fire	Reaction to fire	A1	
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability Characteristics	NPD {a}	
Durability of thermal resistance against heat, weathering, ageing / degradation	Thermal Resistance	NPD{b}	
	Thermal conductivity	NPD	
	Durability characteristics	NPD {c}	
Compressive Strength	Compressive Stress / Compressive Strength	NPD	
	Point Load	NPD	
Tensile / Flexural strength	Tensile strength perpendicular faces	NPD {d}	
Durability of compressive Strength against ageing / degradation	Compressive creep	NPD	
Water Permeability	Short term water absorption	WS	
	Long term water absorption	NPD	
Water vapour permeability	Water vapour transmission, water vapour diffusion resistance factor	MU1	
Impact noise transmissions index (for floors)	Dynamic stiffness	NPD	
	Thickness	NPD	
	Compressibility	NPD	
	Air flow resistivity	NPD	
Acoustic absorptions index	Sound absorption	NPD	
Direct airborne sound insulation index	Air flow resistivity	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD {e}	
Continuous glowing combustion	Continuous glowing combustion	NPD {e}	
NPD - No performance determined			

Essential Characteristics	R4208JPCPR		Harmonised technical standard
	Performance {f}	ROOFMAX 30 PLUS	
Thermal Resistance	Thermal conductivity (W/mK)	λ_D 0,037	EN 13162:2012 + A1:2015
	Thermal Resistance	See performance chart	
	Thickness range (mm)	50-200	
	Thickness tolerance	T4	
Reaction to Fire	Reaction to fire	A1	
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability Characteristics	NPD {a}	
Durability of thermal resistance against heat, weathering, ageing / degradation	Thermal Resistance	NPD{b}	
	Thermal conductivity	NPD	
	Durability characteristics	NPD {c}	
Compressive Strength	Compressive Stress / Compressive Strength	NPD	
	Point Load	NPD	
Tensile / Flexural strength	Tensile strength perpendicular faces	NPD {d}	
Durability of compressive Strength against ageing / degradation	Compressive creep	NPD	
Water Permeability	Short term water absorption	NPD	
	Long term water absorption	NPD	
Water vapour permeability	Water vapour transmission, water vapour diffusion resistance factor	MU1	
Impact noise transmissions index (for floors)	Dynamic stiffness	NPD	
	Thickness	NPD	
	Compressibility	NPD	
	Air flow resistivity	NPD	
Acoustic absorptions index	Sound absorption	NPD	
Direct airborne sound insulation index	Air flow resistivity	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD {e}	
Continuous glowing combustion	Continuous glowing combustion	NPD {e}	
NPD - No performance determined			

Essential Characteristics	R4208JPCPR		Harmonised technical standard
	Performance {f}	RS35 (BLX)	
Thermal Resistance	Thermal conductivity (W/mK)	λ_D 0,037	EN 13162:2012 + A1:2015
	Thermal Resistance	See performance chart	
	Thickness range (mm)	30-<40 40-<50 50-200	
	Thickness tolerance	T2 T2 T4	
Reaction to Fire	Reaction to fire	A1 A1 A1	
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability Characteristics	NPD {a}	
Durability of thermal resistance against heat, weathering, ageing / degradation	Thermal Resistance	NPD{b}	
	Thermal conductivity	NPD	
	Durability characteristics	NPD {c}	
Compressive Strength	Compressive Stress / Compressive Strength	NPD	
	Point Load	NPD	
Tensile / Flexural strength	Tensile strength perpendicular faces	NPD {d}	
Durability of compressive Strength against ageing / degradation	Compressive creep	NPD	
Water Permeability	Short term water absorption	NPD	
	Long term water absorption	NPD	
Water vapour permeability	Water vapour transmission, water vapour diffusion resistance factor	MU1 MU1 MU1	
Impact noise transmissions index (for floors)	Dynamic stiffness	NPD	
	Thickness	NPD	
	Compressibility	NPD	
	Air flow resistivity	NPD AFr5 AFr5	
Acoustic absorptions index	Sound absorption	NPD	
Direct airborne sound insulation index	Air flow resistivity	NPD AFr5 AFr5	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD {e}	
Continuous glowing combustion	Continuous glowing combustion	NPD {e}	
NPD - No performance determined			

Essential Characteristics	R4208JPCPR		Harmonised technical standard
	Performance {f}	TERMOCOFRAGE	
Thermal Resistance	Thermal conductivity (W/mK)	λ_D 0,037	EN 13162:2012 + A1:2015
	Thermal Resistance	See performance chart	
	Thickness range (mm)	50 - 200	
	Thickness tolerance	T5	
Reaction to Fire	Reaction to fire	A1	
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability Characteristics	NPD {a}	
Durability of thermal resistance against heat, weathering, ageing / degradation	Thermal Resistance	NPD{b}	
	Thermal conductivity	NPD	
	Durability characteristics	DS (70,90) {c}	
Compressive Strength	Compressive Stress / Compressive Strength	CS(10)20	
	Point Load	PL(5)300	
Tensile / Flexural strength	Tensile strength perpendicular faces	TR7.5 {d}	
Durability of compressive Strength against ageing / degradation	Compressive creep	NPD	
Water Permeability	Short term water absorption	WS	
	Long term water absorption	WL(P)	
Water vapour permeability	Water vapour transmission, water vapour diffusion resistance factor	NPD	
Impact noise transmissions index (for floors)	Dynamic stiffness	NPD	
	Thickness	NPD	
	Compressibility	NPD	
	Air flow resistivity	NPD	
Acoustic absorptions index	Sound absorption	NPD	
Direct airborne sound insulation index	Air flow resistivity	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD {e}	
Continuous glowing combustion	Continuous glowing combustion	NPD {e}	
NPD - No performance determined			

8. Appropriate Technical Documentation and / or Specific Technical Documentation:

Not applicable

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

[mm]	25	30	35	40	45	50	55	60	65	70	75	80	85	90
[m ² K/W]	0,65	0,80	0,90	1,05	1,20	1,35	1,45	1,60	1,75	1,85	2,00	2,15	2,25	2,40
[mm]	95	100	105	110	115	120	125	130	135	140	145	150	155	160
[m ² K/W]	2,55	2,70	2,80	2,95	3,10	3,20	3,35	3,50	3,60	3,75	3,90	4,05	4,15	4,30
[mm]	165	170	175	180	185	190	195	200	205	210	215	220		
[m ² K/W]	4,45	4,55	4,70	4,85	5,00	5,10	5,25	5,40	5,50	5,65	5,80	5,90		

Signed for an on behalf of the manufacturer by:

Mark Joliffe - Plant manager
(Name and function)



Queensferry - 02-03-22
(Place and date of issue)

- {a} No change in reaction to fire properties for MW Products. The fire performance of MW does not deteriorate with time. The Euroclass classification of the product is related to the organic content, which cannot increase with time.
- {b} Thermal conductivity of MW products does not change with time, experience has shown the fibre structure to be stable and the porosity contains no other gases than atmospheric air
- {c} For dimensional stability thickness only
- {d} This characteristic also covers handling and installation
- {e} European test methods are under development
- {f} Also valid and applicable for multilayers