



- High adhesive strength, stable shape, cannot be over-stretched
- Colour matched to the facade membrane
- Can be exposed to weather for up to 12 months

Packaging

	Box mass [kg]	Roll length [m]	Roll width [mm]	Box contents [units]
PAVAFIX 60	2,8	25	60	4
PAVAFIX 20_40	2,8	25	60	4
PAVAFIX 150	3,2	25	150	2

Characteristics

Material	acrylic adhesive on a synthetic carrier
Thickness [mm]	0,3
Minimum substrate and ambient temperature with PAVAPRIM [°C]	-10
Application temperature product [°C]	-5 to +40
Temperature resistance [°C]	-40 to +90

Product description

PAVAFIX is an all-round acrylate adhesive tape for permanent sealing of PAVATEX membranes and wood-fibre boards indoors and outdoors.

Very high adhesion and good resistance to ageing and water. Can be exposed to weather for up to 12 months. When gluing to porous or mineral surfaces, the primer PAVAPRIM is preliminary applied.

- PAVAFIX 60: For gluing foils
- PAVAFIX 20_40: For gluing connections
- PAVAFIX 150: For bonding ridge, valley, edge and board joints

Always consult the local regulations and installation guidelines of the manufacturer.

Health, Environment and Safety

This product does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements.

Storage

Store cool and dry, protected from sunlight.