

# Metal Corner Tape

<b>ROLL SIZE:</b>	50mm x 30m
<b>QUANTITY PER BOX:</b>	10 Rolls
<b>DESCRIPTION:</b>	Roll of specific craft paper for jointing applications and two flexible anti-corrosion treated steel strips
<b>APPLICATION:</b>	Reinforce outstanding angles of plasterboard applications
<b>INSTRUCTIONS FOR USE:</b>	Make sure that the surface to work on is clean (no dust or grease). Use a taping knife. Coat both side of the angle to reinforce with 3mm of filling compound. Fold the corner tape and set it up firmly. Remove excess filling compound with the taping knife. Re-coat with a finishing joint compound. Once all dried sand lightly with a fine abrasive
<b>TEMPERATURE OF USE:</b>	From 5°C to 30°C
<b>TECHNICAL FEATURES</b> Composition:	Material Body - Kraft paper, zinc plated steel or aluminium coated strips
<b>DIMENSIONS</b> Roll Length: Paper Width: Space between strips:	30m 50mm 1.25mm
<b>TESTS</b> Durability: Paper Flexural Strength: Paper Dimensional Stability:	Anti-corrosion, 48h resistance to salt spray test (NF EN ISO 9227) 5.239 N/mm (NF EN 13963) (NF EN 13963) Length - 0.1% Width - 1.2%
<b>WAREHOUSE RECOMMENDATIONS:</b>	Dry place with a constant temperature between -10°C and +60°C