



## Dune eVo


In every sector from transport to retail, and in every environment from hotels and hospitals to schools and workplaces, Dune eVo is designed to meet all your project needs. Dune eVo is 100% recyclable to meet your sustainability targets.



BRONZE

## Key Features

- // Improved aesthetics with discreet perforations, a smoother finish and a class-leading, fully painted whiteness
- // Enhanced acoustical absorption performance of 0.60  $\alpha_w$  for better acoustic comfort
- // Fully painted, reinforced edges for a more robust tile and greater durability
- // Mix and match modules for increased flexibility and a more complete project solution
- // Easy to handle and re-engineered for a better, easier fit
- // C2C Certification
- // Ideal for every space



Edge Detail	Board	Tegular	MicroLook 90
<b>Thickness (mm)</b>	15	15	15
<b>Modules (mm)</b>	600 x 600 ..... 5460M 1200 x 600 ..... 5461M	600 x 600 ..... 5462M 1200 x 600 ..... 5463M	600 x 600 ..... 5464M 1200 x 600 ..... 5465M
<b>Suspension Systems</b>	Prelude 24 XL <sup>2</sup> / TLS Prelude 24 Sixty <sup>2</sup> XL <sup>2</sup> / TLS	Prelude 24 XL <sup>2</sup> / TLS Prelude 24 Sixty <sup>2</sup> XL <sup>2</sup> / TLS	Prelude 15 TL / XL <sup>2</sup> Interlude HRC XL <sup>2</sup> Silhouette XL <sup>2</sup>

**Colour** Global White

### Sustainability



44



A+



EN 13964 / E1



### Acoustics



EN ISO 354  
& EN ISO 11654



EN ISO 10848-2  
& EN ISO 717-1

	Hz $\alpha_p$									
	$\alpha_w$	D <sub>nfw</sub>	Class	NRC	125	250	500	1000	2000	4000
Board, Tegular, MicroLook 90	0.60	34 dB	C	0.50	0.40	0.40	0.60	0.55	0.55	0.50

### Fire Reaction



Euroclass A2-s1, d0  
EN 13501-1

### Performances & Features



85%



95% RH



3.6 Kg/m<sup>2</sup>



### Custom Options



Colours<sup>1</sup>

<sup>1</sup>See the Colortone range

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email [enquiries@zentia.com](mailto:enquiries@zentia.com)

TDS 043.4.12.22