







Hydroboard ($\leq 100\%$ RH)

Hydroboard can resist permanent RH up to 95% and temporary conditions of up to 100% RH. Install with Prelude 24 Corrosive Resistant grid system for higher humidity areas.

Key Features

- Stable at humidity levels of up to 100% RH
- Can be installed in temperatures ranging from 0°C to 40°C
- High acoustic absorption up to 0.95 α_w
- Ideal for WC, shower areas and hydrotherapy rooms. Should be installed on Corrosive Resistant grid



Edge Detail	Board	Tegular	MicroLook 90
			
Thickness (mm)	15	15	15
Modules (mm)	600 x 600 3687M 1200 x 600 3688M	600 x 600 3689M	600 x 600 3691M
Suspension Systems	Prelude 24 XL ² / TLS Prelude 24 Corrosive Resistant Prelude 24 Sixty ² XL ² / TLS	Prelude 24 XL ² / TLS Prelude 24 Corrosive Resistant Prelude 24 Sixty ² XL ² / TLS	Prelude 15 TL / XL ² Interlude HRC XL ² Silhouette 6mm XL ²
Colour	Global White		

Sustainability



20



EN 13964 / E1

Acoustics



EN ISO 354
& EN ISO 11654



EN ISO 10848-2
& EN ISO 717-1

	Hz α_p									
	α_w	D _{nfw}	Class	NRC	125	250	500	1000	2000	4000
Board	0.95	22 dB	A	0.90	0.35	0.80	1.00	0.85	1.00	1.00
Tegular MicroLook 90	0.90	22 dB	A	0.85	0.40	0.75	0.85	0.85	0.95	0.95

Fire Reaction



A1
EN 13501-1

Performances & Features



82%



≤100% RH



30 Year
System
Guarantee



1.2 Kg/m² Board

2.5 Kg/m² Tegular 90,
MicroLook 90



BIM
READY

While this product is suitable for high humidity environments, it is not suitable to be fitted directly over a swimming pool.

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 041.3.10.22