

OmniFit® Slab 32 and 35

June 2024

Build on us.



Description

OmniFit® Slabs are a range of glass mineral wool slabs designed for use in multiple applications, offering thermal conductivity between 0.032 W/mK and 0.035 W/mK, combined with acoustic performance.

OmniFit® Slabs are non-combustible with the best possible Euroclass A1 reaction to fire classification, and are manufactured using our unique bio-based binder, ECOSE® Technology.

Benefits

- › OmniFit® Slab 35 holds an Agrément certificate by the BBA (under reference number 24/7110) for use as insulation between rainscreen façade systems.
- › Multi-purpose product that can be used to insulate a wide range of applications, reducing the need to purchase and handle multiple products.
- › Designed to friction fit between studs, which prevents air movement and infiltration around the edges, minimising heat loss.
- › Compression packed with more product on a pallet than alternative rock mineral wool products.
- › Manufactured from mineral wool which provides the best levels of sound absorption and reduction compared to other mainstream insulants.



NON-COMBUSTIBLE
INSULATION



OmniFit® Slab 32 and 35

Technical Specifications

OMNIFIT® SLAB 32

Thickness (mm)	Thermal conductivity (W/mK)	Thermal resistance (m ² K/W)	Length (mm)	Width (mm)	Slabs per pack	Area per pack (m ²)	Packs per pallet	Pallet product code
150	0.032	4.65	1200	600	4	2.88	24	787015
140	0.032	4.35	1200	600	4	2.88	24	787010
120	0.032	3.75	1200	600	5	3.60	24	787009
100	0.032	3.10	1200	600	6	4.32	24	787013
90	0.032	2.80	1200	600	6	4.32	24	786999



OMNIFIT® SLAB 35

Thickness (mm)	Thermal conductivity (W/mK)	Thermal resistance (m ² K/W)	Length (mm)	Width (mm)	Slabs per pack	Area per pack (m ²)	Packs per pallet	Pallet product code
150	0.035	4.25	1200	600	4	2.880	32	587280
140	0.035	4.00	1200	600	4	2.880	36	474342
100	0.035	2.85	1200	600	6	4.320	32	474340
90	0.035	2.55	1200	600	6	4.320	36	474337
75	0.035	2.10	1200	600	8	5.760	32	587268
70	0.035	2.00	1200	600	8	5.760	32	474334
50	0.035	1.40	1200	600	12	8.640	24	474329
140	0.035	4.00	1200	400	4	1.920	48	474318
100	0.035	2.85	1200	400	6	2.880	42	474314
50	0.035	1.40	1200	400	12	5.760	36	474293




All dimensions are nominal

OmniFit® Slab 32 and 35


Performance

THERMAL (W/mK)



Euroclass reaction to fire classification

GENERIC BRE GREEN GUIDE RATING



VAPOUR RESISTIVITY



Certification, accreditations and industry standards



*Not OmniFit® Slab 32



Applications



Pitched Roofs Rafter Level



Internal Walls



Frame Construction With Masonry Outer



Suspended Timber Ground Floors



Separating Floors Timber



Internal Floors



Separating Floors Upgrade to an existing timber floor with new ceiling




Separating Floors Upgrade to an existing timber floor with platform floor



Timber Frame Walls Built-in insulation between studs with partially filled cavity





Timber Frame Walls Built-in insulation between studs with low emissivity service void



Rainscreen Façade System



Cold flat roof



OmniFit® Slab 32 and 35

Application

OmniFit® Slabs are typically used for the thermal and acoustic insulation of a wide variety of constructions such as timber and metal stud partitions, timber frame walls, between rafters and timber floors.

Both, OmniFit® Slab 32 and 35 are suitable for use as the inner leaf insulation between light steel frame studwork in a rainscreen façade system or in a steel frame construction with masonry outer leaf.

OmniFit® Slabs are non-combustible.

Standards and certification

OmniFit® Slab 35 has an Agrément certificate by the BBA (under reference number 24/7110) for use as insulation between the studs on timber- and steel-frame conventional walls in new and existing domestic and non-domestic buildings with a masonry outer leaf or a ventilated rainscreen cladding system.*

OmniFit® Slabs have a product declaration made in conformity with the requirements of BS EN 13162 and are manufactured in accordance with ISO 50001 Energy Management Systems, ISO 14001 Environmental Management Systems, ISO 45001 Occupational Health and Safety Management Systems and ISO 9001 Quality Management Systems.

All of our mineral wool products are made of non-classified fibres and are certified by EUCB. EUCB (European Certification Board of Mineral Wool Products - www.euceb.org) is a voluntary initiative by the mineral wool industry. It is an independent certification authority that guarantees that products are made of fibres which comply with the exoneration criteria for carcinogenicity (Note Q) of the Regulation (EC) 1272/2008.

Thermal Modelling

The U-value of a proprietary built element (rainscreen façade/ masonry cavity wall/garage soffit etc.) or system is dependent on the material properties and the degree of thermal bridging in the system. Calculations should be created using 2D or 3D modelling programs which comply with the methodologies detailed in BS EN ISO 6946 or BS EN ISO 10211 and using guidance from BR443.

We offer simplified calculations to BS EN ISO 6946 and where required numerically modelled U-value calculations using software that is compliant with BS EN ISO 10211.

System Testing

Knauf Insulation maintains declared product characteristics and qualities which are defined in detail in its Declaration of Performance (DoPs) and product literature. The product literature also includes information relating to Knauf Insulation's requirements and recommendations for installation of its products when being used as part of a system.

Any party using, or planning to use, our products in a system (with or without system testing) where performance may be dependent on product characteristics not declared on our DoPs or our product literature, must contact our Technical Service Team.

Knauf Insulation will not accept liability for any failure in system performance due to product characteristics not declared on DoPs or product literature, or not agreed in a Service Level Agreement. In such an event, any warranty given in relation to those products will be invalidated.

Real Performance

Glass and rock mineral wool are easier to install correctly than other insulants, such as rigid boards, because they adapt to any slight imperfections in the substrate and knit together, eliminating any air gaps. Mineral wool is engineered to adapt to any imperfections, and any settlement/movement over time, so it maintains close contact and preserves thermal performance for the life of the building.

Evidence shows the absence of air gaps is crucial to achieving real performance in the relevant application. Any insulation material that doesn't deliver 'as-built' thermal performance is failing in its primary purpose, and therefore presents an unnecessary risk as the construction industry seeks to close the performance gap.

Durability

OmniFit® Slabs are odourless, rot proof, non-hygroscopic, do not sustain vermin and will not encourage the growth of fungi, mould or bacteria. The products will have a life equivalent to that of the structure in which they are incorporated.

* Please note, only the applications described within the above Agrément certificate by the BBA is covered. OmniFit® Slab 32 is not currently covered by the Agrément certificate by the BBA (under reference number 24/7110).

OmniFit® Slab 32 and 35

Sustainability

OmniFit® Slabs are manufactured with ECOSE® Technology, our unique bio-based binder which contains no added formaldehyde or phenol. It is made from natural raw materials that are rapidly renewable and is less energy-intensive to manufacture than traditional binders. Products made with ECOSE® Technology are soft to touch and easy to handle. They generate low levels of dust and VOCs and have been awarded the Eurofins Gold Certificate for Indoor Air Comfort.

All our glass mineral wool products have been awarded the DECLARE 'Red List Free' label. The Declare label is a third-party accreditation and is similar to a food nutrition label but for building products; it is a straightforward ingredient list and allows product transparency disclosure because it identifies where a product comes from and what it is made of. Declare 'Red List Free' certifies that there is no harmful chemical from the red list in these products.

Our glass mineral wool is made with up to 80% recycled content (including glass from windows, bottles and jars).

OmniFit® Slabs contain no ozone-depleting substances or greenhouse gases. The overall environmental performance of our products is reported in their EPDs (Environmental Product Declarations) which are available on our website. EPDs are available for all our products in accordance with ISO 14025, ISO 21930 and EN 15804+A2.

We have received the BES6001 'Very Good' rating for all our mineral wool in our three plants, which proves that our products are made with constituent materials that are responsibly sourced.

Our 3-tier industry-leading compression-packaging technology allows us to load more product per pack or pallet, and therefore onto each truck that leaves our factories. This means less packaging used per m² of insulation, fewer vehicles on our roads, so less associated CO₂ emissions. It also means less transport, handling and storage space required for our customers.

Our individual products and the pallets they sit on are wrapped in low-density polyethylene (LDPE4) plastic, which is made of 30-50% (depending on the supplier) recycled plastic content and is fully recyclable.

Handling & Storage

OmniFit® Slabs should be stored properly and handled in such a way as to ensure that the products remain clean and undamaged.

The polyethylene packs / shrink-wrapped pallets used for the supply of OmniFit® Slabs are designed for short-term protection only. For longer term protection on site, the product should either be stored indoors or under cover and off the ground. OmniFit® Slabs should not be left permanently exposed to the elements.

If the main hood is removed or damaged, the remaining packs should be kept under cover indoors or protected from the elements by a weatherproof cover. In coastal locations where weather is more extreme and bird damage is more common, use additional covering or store indoors.

The product must be protected from prolonged exposure to sunlight and stored dry and flat.

OmniFit® Slabs are light and easy to handle; care should be exercised to avoid crushing their edges or corners. If damaged, the product should be discarded. Damaged, contaminated or wet products must not be used.

During construction exposed areas of slabs should always be covered at the end of a day's work or in heavy rain. Polyethylene covers should be used to provide protection and prevent work from becoming saturated.

Knauf Insulation Ltd

Stafford Road, St.Helens, Merseyside, WA10 3LZ Customer Service: 01744 766 766

All rights reserved, including those of photomechanical reproduction and storage in electronic media. Extreme caution was observed when putting together and processing the information, text and illustrations in this document. Nevertheless, errors cannot be completely ruled out. The publisher and editors cannot assume legal responsibility or any liability for incorrect information and consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of possible errors pointed out. For the most up-to-date document versions and product information, please always refer to our website.