

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Revision date: 10/6/2022 Supersedes version of: 8/24/2022 Version: 2.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : PROMASEAL® INTUMESCENT ACRYLIC SEALANT
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Industrial/Professional use spec : For professional use only
Use of the substance/mixture : Barrier (Sealant)

1.2.2. Uses advised against

No additional information available.

1.3. Details of the supplier of the safety data sheet

Supplier

Etex Building Performance Limited
Gordano House, Marsh Lane, Easton-in-Gordano
Eastern Road
BS20 ONE Bristol - UNITED KINGDOM
T +44 (0800) 373 636
marketinguk@promat.co.uk - www.promat.co.uk

Other

Etex Middle East LLC
Plot No. 597-921 Dubai Investment Park 2
123945 Dubai - UNITED ARAB EMIRATES
T +971 4 885 3070 - F +971 4 885 3588
info@promatfp.ae - www.promat.com

Other

Promat International (Asia Pacific) Ltd.
Room 1010, C.C Wu Building, 302-308 Hennessy Road
Wanchai
T +852 2836 3692 - F +852 2834 4313
promat.hk@etexgroup.com

1.4. Emergency telephone number

Emergency number : Please contact a regional poison center or emergency telephone number.

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

PROMASEAL® INTUMESCENT ACRYLIC SEALANT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one(2634-33-5), reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7], and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)(55965-84-9). May produce an allergic reaction.
EUH210 - Safety data sheet available on request.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not established.

3.2. Mixtures

Comments : Mixture of the substances listed below with harmless additives

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Calcium carbonate substance with national workplace exposure limit(s) (GB)	(CAS-No.) 471-34-1 (EC-No.) 207-439-9	30 – 50	Not classified
Aluminium hydroxide, Aluminium trihydrate substance with national workplace exposure limit(s) (GB)	(CAS-No.) 21645-51-2 (EC-No.) 244-492-7	10 – 30	Not classified
1,2-benzisothiazol-3(2H)-one	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9 (EC Index-No.) 613-088-00-6	< 0.05	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400
Reaction mass of 2-methyl-2H-isothiazol-3-one and 5-chloro-2-methyl-2H-isothiazol-3-one	(CAS-No.) 55965-84-9 (EC Index-No.) 613-167-00-5	< 0.0015	Acute Tox. 2 (Inhalation), H330 Acute Tox. 2 (Dermal), H310 Acute Tox. 3 (Oral), H301 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)

Specific concentration limits:

Name	Product identifier	Specific concentration limits
1,2-benzisothiazol-3(2H)-one	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9 (EC Index-No.) 613-088-00-6	(0.05 ≤C ≤ 100) Skin Sens. 1, H317

PROMASEAL® INTUMESCENT ACRYLIC SEALANT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Reaction mass of 2-methyl-2H-isothiazol-3-one and 5-chloro-2-methyl-2H-isothiazol-3-one	(CAS-No.) 55965-84-9 (EC Index-No.) 613-167-00-5	(0.0015 ≤C ≤ 100) Skin Sens. 1A, H317 (0.06 ≤C < 0.6) Skin Irrit. 2, H315 (0.06 ≤C < 0.6) Eye Irrit. 2, H319 (0.6 ≤C ≤ 100) Eye Dam. 1, H318 (0.6 ≤C ≤ 100) Skin Corr. 1C, H314
---	---	--

Comments : The product does not contain any substances of very high concern (SVHC).
Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Seek medical attention if irritation or symptoms persist.
First-aid measures after skin contact : Wash skin with plenty of water and soap. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact : Immediately rinse with water for a prolonged period while holding the eyelids wide open. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Rinse mouth. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Immediate effects can be expected after short term exposure.
Symptoms/effects after inhalation : May cause irritation to the respiratory tract and to other mucous membranes.
Symptoms/effects after skin contact : May produce skin irritation.
Symptoms/effects after eye contact : May cause eye irritation.
Symptoms/effects after ingestion : May cause irritation to the digestive tract.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : When heated to decomposition, emits toxic fumes.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin and eyes.

6.1.1. For non-emergency personnel

Protective equipment : Wear personal protective equipment.
Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

PROMASEAL® INTUMESCENT ACRYLIC SEALANT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.2. Environmental precautions

Do not allow entry to drains, sewers, water courses or soil.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Wash contaminated area with large amounts of water.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid dust formation. Provide adequate general and local exhaust ventilation. Do not breathe dust. Use always respiratory protective equipment when exposures are likely or can be foreseen to exceed the Occupational Exposure Limits or Workplace Exposure Limits in the UK (refer to local regulations). Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety procedures.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a cool, well-ventilated place.

7.3. Specific end use(s)

No additional information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Calcium carbonate (471-34-1)	
United Kingdom - Occupational Exposure Limits	
Local name	Calcium carbonate (Limestone, Marble)
WEL TWA (OEL TWA) [1]	10 mg/m ³ total inhalable 4 mg/m ³ respirable
WEL STEL (OEL STEL)	4 mg/m ³
Regulatory reference	EH40/2005 (Forth edition, 2020), HSE

Aluminium hydroxide, Aluminium trihydrate (21645-51-2)

United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	10 mg/m ³
WEL STEL (OEL STEL)	4 mg/m ³

8.1.2. Recommended monitoring procedures

No additional information available.

8.1.3. Air contaminants formed

No additional information available.

PROMASEAL® INTUMESCENT ACRYLIC SEALANT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.4. DNEL and PNEC

No additional information available.

8.1.5. Control banding

No additional information available.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure. Dust formation: dust mask.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses. Foresee eye cleaning on the workplace.

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

Use appropriate respiratory equipment when exposures are likely or can be foreseen to exceed the Occupational Exposure Limits or Workplace Exposure Limits for the UK (e.g. for exposures up to 10 times the OEL (WEL) use at least a P2 type dust mask. For higher exposure, use a P3 type mask).

8.2.2.4. Thermal hazards

No additional information available.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment. Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Colour	: white.
Appearance	: Paste.
Odour	: Mild.
Odour threshold	: Not available

PROMASEAL® INTUMESCENT ACRYLIC SEALANT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Melting point	: Not available
Freezing point	: Not applicable
Boiling point	: Not available
Flammability	: Non flammable.
Explosive limits	: Not applicable
Lower explosion limit	: Not applicable
Upper explosion limit	: Not applicable
Flash point	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: Not available
pH	: 6.5 – 9
pH solution	: Not available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: 300000 – 900000 cP
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 1.56 – 1.66 g/cm ³
Relative density	: Not available
Relative vapour density at 20 °C	: Not applicable
Particle size	: Not available
Particle size distribution	: Not available
Particle shape	: Not available
Particle aspect ratio	: Not available
Particle aggregation state	: Not available
Particle agglomeration state	: Not available
Particle specific surface area	: Not available
Particle dustiness	: Not available

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available.

9.2.2. Other safety characteristics

Percent Solids : Not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids.

10.6. Hazardous decomposition products

No decomposition if stored and applied as directed. When heated to decomposition, emits toxic fumes.

PROMASEAL® INTUMESCENT ACRYLIC SEALANT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Calcium carbonate (471-34-1)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))

Aluminium hydroxide, Aluminium trihydrate (21645-51-2)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)

Skin corrosion/irritation : Not classified
pH: 6.5 – 9
Serious eye damage/irritation : Not classified
pH: 6.5 – 9
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

Aluminium hydroxide, Aluminium trihydrate (21645-51-2)	
NOAEL (animal/male, F0/P)	1000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure : Not classified
STOT-repeated exposure : Not classified

Calcium carbonate (471-34-1)	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Aluminium hydroxide, Aluminium trihydrate (21645-51-2)	
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.07 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

Aspiration hazard : Not classified

PROMASEAL® INTUMESCENT ACRYLIC SEALANT	
Viscosity, kinematic	Not applicable

11.2. Information on other hazards

No additional information available.

PROMASEAL® INTUMESCENT ACRYLIC SEALANT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Ecology - water	: Do not allow into drains or water courses.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Calcium carbonate (471-34-1)

EC50 72h - Algae [1]	> 14 mg/l Test organisms (species): <i>Desmodesmus subspicatus</i> (previous name: <i>Scenedesmus subspicatus</i>)
----------------------	---

12.2. Persistence and degradability

PROMASEAL® INTUMESCENT ACRYLIC SEALANT

Persistence and degradability	Biodegradable.
-------------------------------	----------------

12.3. Bioaccumulative potential

PROMASEAL® INTUMESCENT ACRYLIC SEALANT

Bioaccumulative potential	No bioaccumulation.
---------------------------	---------------------

12.4. Mobility in soil

PROMASEAL® INTUMESCENT ACRYLIC SEALANT

Ecology - soil	Readily absorbed into soil.
----------------	-----------------------------

12.5. Results of PBT and vPvB assessment

PROMASEAL® INTUMESCENT ACRYLIC SEALANT

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Endocrine disrupting properties

No additional information available.

12.7. Other adverse effects

Other adverse effects	: Negligible ecotoxicity
-----------------------	--------------------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
European List of Waste (LoW) code	: Please refer to the European list (Decision N° 2000/532/CE) to identify the wastes appropriate waste number.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

PROMASEAL® INTUMESCENT ACRYLIC SEALANT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.1. UN number or ID number

UN-No. (ADR)	: Not regulated.
UN-No. (IMDG)	: Not regulated.
UN-No. (IATA)	: Not regulated.
UN-No. (ADN)	: Not regulated.
UN-No. (RID)	: Not regulated.

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: Not regulated.
Proper Shipping Name (IMDG)	: Not regulated.
Proper Shipping Name (IATA)	: Not regulated.
Proper Shipping Name (ADN)	: Not regulated.
Proper Shipping Name (RID)	: Not regulated.

14.3. Transport hazard class(es)

ADR	
Transport hazard class(es) (ADR)	: Not regulated.
IMDG	
Transport hazard class(es) (IMDG)	: Not regulated.
IATA	
Transport hazard class(es) (IATA)	: Not regulated.
ADN	
Transport hazard class(es) (ADN)	: Not regulated.
RID	
Transport hazard class(es) (RID)	: Not regulated.

14.4. Packing group

Packing group (ADR)	: Not regulated.
Packing group (IMDG)	: Not regulated.
Packing group (IATA)	: Not regulated.
Packing group (ADN)	: Not regulated.
Packing group (RID)	: Not regulated.

14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

14.6. Special precautions for user

Overland transport

Not regulated.

Transport by sea

Not regulated.

Air transport

Not regulated.

Inland waterway transport

Not regulated.

Rail transport

Not regulated.

14.7. Maritime transport in bulk according to IMO instruments

Not established.

PROMASEAL® INTUMESCENT ACRYLIC SEALANT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list.

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants.

15.1.2. National regulations

No additional information available.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

1.4. Emergency phone number.

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration

PROMASEAL® INTUMESCENT ACRYLIC SEALANT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Other information : A safety data sheet is not required for this product under Article 31 of REACH. The safety data sheet has been created on a voluntary basis.

Full text of H- and EUH-statements:	
Acute Tox. 2 (Dermal)	Acute toxicity (dermal), Category 2
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
EUH208	Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one(2634-33-5), reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7], and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)(55965-84-9). May produce an allergic reaction.
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

PROMASEAL® INTUMESCENT ACRYLIC SEALANT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A

Safety information applicable for : IE;GB
regions

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.