

DECLARATION OF PERFORMANCE Aqua Board

No. UKSI-15283-002

1. Unique identification code of the product-type:

Aqua Board (Gypsum board with mat reinforcement Type GM-F, GM-H1, & GM-I)

2. Intended use/es:

General building construction

3. Manufacturer:

Siniat, Etex Building Performance Limited, Marsh Lane, Easton-in-Gordano, Bristol, BS20 ONE, UK

4. Not applicable

5. System/s of AVCP:

Systems 3 and 4

6a. Harmonised standard: EN 15283-1:2008+A1:2009

Notified Body/ies: CSTB (NB 0679) Performed: Reaction to fire Under: System 3

6b. Not applicable

7. Declared performance/s:

Essential Characteristics		Performance		Harmonised Technical Specification
Shear Strength - ↑↓		NPD		
Reaction To Fire - R2F		A2-s1,d0		EN 13501-1:2007 + A1:2009
Stability of Ceiling Elements - ↓		NPD		
Flexural Strength- F		Transverse:	Longitudinal:	
1	.2.5mm	≥210N	≥538N	EN 15283-1:2008+A1:2009
1	.5mm	≥252N	≥645N	
Water Vapour Permeability – μ		10		EN ISO 12572: 2001
Thermal Conductivity – λ		0.25 W/m.K		EN ISO 12572: 2001
Impact Resistance - →		see manufacturers literature		
Direct Airborne Sound Insulation - R				
Acoustic Absorption - α				

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

ORIGINAL DECLARATION:

Signed for and on behalf of Siniat Limited by: Jean-Michel Desmoutier, Managing Director Bristol, 01/07/2013



REVIEWED DECLARATION:

Signed for and on behalf of Etex Building Performance Limited by: Nigel Morrey, Technical Director Bristol, UK, 21/06/2019



Please check that this is the current version by visiting the Siniat website. For archived versions please contact technical services.

