

Description

GTEC Fire Board is for use in areas where improved fire resistance is required. The board is stronger, harder and heavier than Standard plasterboard and has superior fire resistance in GTEC Drywall Systems.

Appearance

The GTEC Fire Board is coloured pink on the front and grey on the back, and has tapers down the long edges (some 12.5 mm formats available in square edge).

Name and batch number of the board is written at the back and on the long edges of the board.

Composition

Aerated Calcium sulphate di-hydrate with fillers and fibres enclosed inside liners made from recycled waste paper with bound edges. Core and papers are bonded with starch. Edge glue is PVA.

Compliance

GTEC Fire Board complies with BS EN 520:2004+A1:2009 Type D & F.

Physical Properties

Flexural Strength to BS EN 520:

12.5 mm board

Longitudinal breaking load $\geq 550N$

Transverse breaking load $\geq 210N$

15.0 mm board

Longitudinal breaking load $\geq 650N$

Transverse breaking load $\geq 250N$

Fire, acoustic & duty performance dependent on the whole system. See Siniat Drywall Manual for Siniat system performances.

Reaction to fire:

Euroclass A2-s1, d0

Moisture Content:

< 2%

Mass:

10.2 kg/m² for 12.5 mm board

12.3 kg/m² for 15.0 mm board

Board weight:

29.4 kg for 2400 mm x 1200 mm x 12.5 mm board

35.4 kg for 2400 mm x 1200 mm x 15.0 mm board

Thermal Conductivity, λ_R :

0.25 W/mK to BS EN 12524:2000

Thermal Resistance, R:

12.5 mm = 0.050 m²K/W

15.0 mm = 0.060 m²K/W

Mean Water vapour resistance factor:

$\mu = 10$ to BS EN 12524

Handling & Fixing

GTEC Fire Board may be cut using the 'score and snap' method. No power tools are required.

Fixings must be suitable for the intended substrate:

GTEC Self Tapping Screws for attaching plasterboard to thin gauge metal (up to 0.7 mm);

GTEC Self Drilling Screws for attaching plasterboard to thick gauge metal (up to 2.5 mm);

GTEC High Thread Screws for attaching plasterboard to timber.

Jointing Finishing & Painting

GTEC Fire Board should be jointed and finished with GTEC Jointing systems. Boards are suitable for gypsum finishing plasters manufactured to BS EN 13279-1:2008. Boards require priming with GTEC Universal Sealer prior to decorating.

Health & Safety

Please refer to the Plasterboard Health and Safety Datasheet available on our website.

Individual board weight values may occasionally exceed nominal weights published in this datasheet.

09/12/2019 RC

Please check that this is the current version by visiting the Siniat website. For archived versions please contact technical services.

ETEX BUILDING PERFORMANCE LIMITED

Gordano House, Marsh Lane, Easton-in-Gordano, Bristol, BS20 0NE
Technical Services | T: +44 (0)800 145 6033 or +44 (0)1275 377 789
E: technical.siniat@etexbp.co.uk
www.siniat.co.uk